

This Product MasterSpec Section is licensed by Deltek, Inc. to Rubbermaid Incorporated; a Newell Brands company ("Licensee").

**This independent Product MasterSpec Section uses original MasterSpec text.**

Revisions made to the original MasterSpec text are made solely by the Licensee and are not endorsed by, or representative of the opinions of, Deltek or The American Institute of Architects (AIA). Neither AIA nor Deltek are liable in any way for such revisions or for the use of this Product MasterSpec Section by any end user. A qualified design professional should review and edit the document to suit project requirements.

For more information, contact Rubbermaid Incorporated; a Newell Brands company; 8900 North Pointe Executive Dr., Huntersville, NC 28078; Phone: (888) 895-2110; Fax: (573) 204-2615; Website: <http://rubbermaidpro.com>; Email: [sales-info@closetdesignpro.zendesk.com](mailto:sales-info@closetdesignpro.zendesk.com).

For information about MasterSpec, contact Deltek at (800) 424-5080 or visit [masterspec.com](http://masterspec.com).

## SECTION 105723 - CLOSET AND UTILITY SHELVING

### **TIPS:**

To view non-printing **Editor's Notes** that provide guidance for editing, click on MasterWorks/Single-File Formatting/Toggle/Editor's Notes.

To read **detailed research, technical information about products and materials, and coordination checklists**, click on MasterWorks/Supporting Information.

### **Access Product MasterSpec Sections:**

[<Double click here to view the list of manufacturer Sections available at ProductMasterSpec.com.>](#)

## PART 1 - GENERAL

### 1.1 SUMMARY

#### A. Section Includes:

1. Custom wood storage systems.

#### B. Related Requirements:

1. Section 061000 "Rough Carpentry" for furring, blocking, and other carpentry work not exposed to view[ **and for framing exposed to view**].
2. Section 061053 "Miscellaneous Rough Carpentry" for furring, blocking, and other carpentry work not exposed to view.

## 1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product. Indicate component materials, dimensions, profiles, textures, and colors and include construction and application details.
- B. Sustainable Design Submittals:
  - 1. Product Data: For recycled content, indicating postconsumer and preconsumer recycled content and cost.
  - 2. Composite Wood Products: Verify products are made using ultra-low-emitting formaldehyde resins, as defined in the California Air Resources Board's "Airborne Toxic Control Measure to Reduce Formaldehyde Emissions from Composite Wood Products," or are made with no added formaldehyde.
- C. Shop Drawings:
  - 1. Include plans, elevations, sections, and details.
  - 2. Show shelving and accessory layout.
  - 3. Indicate products by description and item part number.
- D. Samples: For each exposed product and for each color and texture specified.
- E. Samples for Initial Selection: For each type of product involving selection of colors, profiles, or textures.
- F. Samples for Verification: For the following products, one of each, in manufacturer's **[standard]** **[full]** size:
  - 1. For each type of specialized shelving.
  - 2. For each finish system and color of panel products with factory-applied finish.

## 1.3 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For Installer.
- B. Sample Warranty: For manufacturer's special warranty.

## 1.4 QUALITY ASSURANCE

- A. Installer Qualifications: An entity that employs installers and supervisors who are trained and approved by manufacturer.

## 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Stack panel products flat with spacers between each bundle to provide air circulation.
  - 1. Protect materials from weather by covering with waterproof sheeting, securely anchored.
  - 2. Provide for air circulation around stacks and under coverings.

- B. Deliver materials only when environmental conditions comply with requirements specified for installation areas. If materials must be stored in other than installation areas, store only where environmental conditions comply with requirements specified for installation areas.

## 1.6 FIELD CONDITIONS

- A. Environmental Limitations: Do not deliver or install materials until building is enclosed and weatherproof, wet-work in space is completed and nominally dry, and HVAC system is operating and maintaining temperature and relative humidity at occupancy levels during the remainder of the construction period.
- B. Do not install materials that are wet, moisture damaged, or mold damaged.
  - 1. Indications that materials are wet or moisture damaged include, but are not limited to, discoloration, sagging, or irregular shape.
  - 2. Indications that materials are mold damaged include, but are not limited to, fuzzy or splotchy surface contamination and discoloration.

## 1.7 WARRANTY

- A. Special Warranty: Manufacturer agrees to repair or replace components of closet and utility shelving systems that fail in materials or workmanship within specified warranty period.
  - 1. Failures include, but are not limited to, the following:
    - a. Deterioration of metals, metal finishes, and other materials beyond normal wear.
  - 2. Warranty Period: Limited lifetime from date of Substantial Completion.

## PART 2 - PRODUCTS

### 2.1 MANUFACTURERS

- A. Source Limitations: Obtain closet and utility shelving systems from single manufacturer.

### 2.2 MATERIALS, GENERAL

- A. Composite Wood Products: Products shall be made using ultra-low-emitting formaldehyde resins as defined in the California Air Resources Board's "Airborne Toxic Control Measure to Reduce Formaldehyde Emissions from Composite Wood Products" or shall be made with no added formaldehyde.
- B. Melamine-Faced Particleboard: Particleboard complying with ANSI A208.1, Grade M-2, finished on both faces with thermally fused, melamine-impregnated decorative paper and complying with NEMA LD 3, Grade VGL, for Test Methods 3.3, 3.4, 3.6, 3.8, and 3.10.

- C. Cold-Rolled Steel Channels: ASTM A653, structural steel Grade 80; hot-dip galvanized steel, **0.060-inch (1.5-mm)** minimum base-steel thickness.

## 2.3 CUSTOM WOOD LAMINATE STORAGE SYSTEMS

- A. Basis-of-Design Product: Subject to compliance with requirements, provide Rubbermaid Incorporated; a Newell Brands company; Rubbermaid [**Melamine Closet System**].

- B. Laminate Shelving Panels: Melamine-faced particleboard with applied-PVC edge banding, **0.039 inch (1 mm)** thick:

1. Style: [**Flat**] [**Shaker**] [**Raised**].
2. Support: [**Floor**] [**Wall**] mount.
3. Shelf Loading Capacity: [**40 lb (18 kg)**] [**50 lb (23 kg)**] [**55 lb (25 kg)**] [**70 lb (32 kg)**] [**90 lb (41 kg)**] [**100 lb (45 kg)**] [**120 lb (54 kg)**] [**140 lb (63.5 kg)**].
4. Partition Height: [**18 inches (457 mm)**] [**30 inches (762 mm)**] [**48 inches (1219 mm)**] [**72 inches (1829 mm)**] [**84 inches (2134 mm)**] [**96 inches (2438 mm)**] [**As indicated on Drawings**] [**As selected by Architect**].
5. Shelf Length: [**18 inches (457 mm)**] [**24 inches (610 mm)**] [**30 inches (762 mm)**] [**36 inches (914 mm)**] [**As indicated on Drawings**] [**As selected by Architect**].
6. Depth: [**12 inches (305 mm)**] [**14 inches (356 mm)**] [**19 inches (483 mm)**] [**As indicated on Drawings**] [**As selected by Architect**].

- C. Hardware:

1. Style:
  - a. Basis-of-Design Product: Subject to compliance with requirements, provide Rubbermaid Incorporated; a Newell Brands company; Rubbermaid [**Classic**] [**Knob**] [**Modern**].
2. Fasteners: Screws, anchors, brackets, and other devices of type, size, material, and finish for secure attachment; concealed where possible.

- D. Accessories:

1. Base moulding.
2. Clothes Hanging Rods: [**Round**] [**Oval**].
3. Crown moulding.
4. Door kit.
5. Drawer kit with wood dovetailed boxes.
6. Shoe cubbies.
7. Shoe shelves.
8. Tie and belt racks.
9. Valet rods.
10. Hamper kit with integrated baskets; **24 inches (610 mm)** wide; **23-9/16 inches (598 mm)** high.

11. Basket kit; chrome finish; [18 inches (457 mm)] [24 inches (610 mm)] [30 inches (762 mm)] wide; [6 inches (152 mm)] [11 inches (279 mm)] [17 inches (432 mm)] high; 12 inches (356 mm) deep.
12. Hutch kit.
13. Island kit.
14. Closet rods, extendable 24 to 48 inches (610 to 1219 mm).
15. Shelf, single 22 inches (559 mm) long.

E. Finishes:

1. System Finish: [White] [Cherry] [Dunbar gray] [Ivory] [Matte gray] [Mahogany] [As selected by Architect].
2. Metal Finish: Pretreated iron-phosphate coated steel components with chrome finish.
3. Laminate Shelving Panel Color: [White] [Cherry] [Chestnut oak] [Driftwood gray] [Ivory] [Mahogany] [Matte gray] [As selected by Architect].

### PART 3 - EXECUTION

#### 3.1 EXAMINATION

- A. Examine areas, with Installer present, for compliance with requirements for installation tolerances, location of framing and reinforcements, and other conditions affecting performance of shelving systems.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

#### 3.2 INSTALLATION

- A. Install shelving units, accessories, and system components after other finishing operations, including painting, have been completed in area of installation.
- B. Attach shelving units, accessories, and system components to substrates at locations indicated on Drawings in accordance with manufacturer's written instructions.
  1. Level and plumb shelving units to a tolerance of 1/8 inch in 96 inches (3 mm in 2438 mm).

#### 3.3 CLEANING AND PROTECTING

- A. Repair or remove and replace defective work as directed on completion of installation.
- B. Clean finished surfaces, touch up as required, and remove or refinish damaged or soiled areas to match original factory finish, as approved by Architect.
- C. Protect installed products from damage during remainder of construction period.

END OF SECTION 105723